

Version: 2.3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 03/09/2017 Revision date: 04/21/2022 Supersedes: 01/02/2018

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Trade name : Summit Supply® Summit Metal Safe Detergent

Product code : 0372-SL

1.2. Recommended use and restrictions on use

Recommended use : Machine dishwashing products

1.3. Supplier

Synthetic Labs 24 Victory Lane

Dracut, MA 01826 - United States T 800.255.4050 - F 978.957.5122

www.syntecpro.com

1.4. Emergency telephone number

Emergency number : Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Corrosive to metals Category 1
Acute toxicity (oral) Category 4
Skin corrosion/irritation Category 1A
Serious eye damage/eye irritation Category 1
Specific target organ toxicity — Single exposure,
Category 3, Respiratory tract irritation

May be corrosive to metals Harmful if swallowed

Causes severe skin burns and eye damage

Causes serious eye damage May cause respiratory irritation

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : May be corrosive to metals

Harmful if swallowed

Causes severe skin burns and eye damage

Causes serious eye damage May cause respiratory irritation

Precautionary statements (GHS US) : Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center or doctor if you feel unwell.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Call a poison center or doctor if you feel unwell.

Specific treatment (see supplemental first aid instruction on this label).

Rinse mouth.

Wash contaminated clothing before reuse.

04/21/2022 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Absorb spillage to prevent material-damage.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Disodium Metasilicate	(CAS-No.) 6834-92-0	50 – 60	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 STOT SE 3, H335
Sodium Tripolyphosphate	(CAS-No.) 7758-29-4	5 – 10	Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

04/21/2022 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container.

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible materials : Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Summit Supply® Summit Metal Safe Detergent

No additional information available

Sodium Tripolyphosphate (7758-29-4)

No additional information available

Disodium Metasilicate (6834-92-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

04/21/2022 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Solid **Appearance** Powder. Color white Odor odorless

Odor threshold No data available pН No data available

pH solution

12 - 13No data available Melting point Freezing point : Not applicable Boiling point No data available Flash point : Not applicable Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Non flammable. : No data available Vapor pressure Relative vapor density at 20 °C No data available Relative density : Not applicable Soluble in water. Solubility Partition coefficient n-octanol/water (Log Pow) : No data available : Not applicable Auto-ignition temperature Decomposition temperature No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosion limits** Not applicable Explosive properties : No data available Oxidizing properties : No data available

Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. **Chemical stability**

Stable under normal conditions.

Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

04/21/2022 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cording to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (oral)	Harmful if swallowed.	
Acute toxicity (dermal)	Not classified	
Acute toxicity (inhalation)	Not classified	
ATE US (oral)	1540 mg/kg body weight	
Sodium Tripolyphosphate (7758-29-4)		
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 4640 mg/kg body weight (24 h, Rabbit, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 0.39 mg/l (EPA OPP 81-3: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 14 day(s))	
Disodium Metasilicate (6834-92-0)		
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))	
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))	
Skin corrosion/irritation :	Causes severe skin burns.	
Serious eye damage/irritation :	Causes serious eye damage.	
Respiratory or skin sensitization :	Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	

Disodium Metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1	To	XIC	ity

STOT-single exposure

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

: May cause respiratory irritation.

Sodium Tripolyphosphate (7758-29-4)	
LC50 fish 1	> 1850 mg/l (AFNOR, 24 h, Danio rerio, Fresh water, Experimental value)
EC50 Daphnia 1	> 100 mg/l (EPA OTS 797.1930, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	160 mg/l (ISO 8692, 4 day(s), Desmodesmus subspicatus, Fresh water, Experimental value)
Disodium Metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Sodium Tripolyphosphate (7758-29-4)		
Persistence and degradability	Biodegradability: not applicable.	
04/21/2022	EN (English US)	5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium Tripolyphosphate (7758-29-4)		
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
Disodium Metasilicate (6834-92-0)		
Disodium Metasilicate (6834-92-0)		
Disodium Metasilicate (6834-92-0) Persistence and degradability	Biodegradability: not applicable.	
,	Biodegradability: not applicable. Not applicable (inorganic)	

12.3. Bioaccumulative potential

Sodium Tripolyphosphate (7758-29-4)	
Bioaccumulative potential	Not bioaccumulative.
Disodium Metasilicate (6834-92-0)	

12.4. Mobility in soil

Sodium Tripolyphosphate (7758-29-4)		
Partition coefficient n-octanol/water (Log Koc)	2.15 (log Koc, Experimental value)	
Ecology - soil	Low potential for adsorption in soil.	
Disodium Metasilicate (6834-92-0)		
Surface tension	No data available in the literature	
Ecology - soil	Low potential for adsorption in soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1759 Corrosive solids, n.o.s. (Sodium Metasilicate), 8, II

UN-No.(DOT) : UN1759

 $Proper \ Shipping \ Name \ (DOT) \\ \hspace{2cm} : \ Corrosive \ solids, \ n.o.s.$

Sodium Metasilicate

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 213 DOT Packaging Bulk (49 CFR 173.xxx) : 240

DOT Symbols : G - Identifies PSN requiring a technical name

04/21/2022 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 128 - Regardless of the provisions of §172.101(c)(12), aluminum smelting by-products and aluminum remelting by-products described under this entry, meeting the definition of Class 8, Packing Group II and III may be classed as a Division 4.3 material and transported under this entry. The presence of a Class 8 hazard must be communicated as required by this Part for subsidiary hazards

IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

T1 - 1.5 178.274(d)(2) Normal...... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : 25 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 100 kg

CFR 175.75)

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 154

Other information

: No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Sodium Tripolyphosphate (7758-29-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Disodium Metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Sodium Tripolyphosphate (7758-29-4)

Listed on the Canadian DSL (Domestic Substances List)

Disodium Metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

04/21/2022 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Sodium Tripolyphosphate(7758-29-4)	U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/21/2022

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

04/21/2022 EN (English US) 8/8